

適用於600V以下可攜帶式電機具電力電纜之用

(General date for cable type 2 CT(CNS-10741 1999))

Type 型號	Conductor		Insulation	Jacket被覆體								Max.	Insulation	Approval
	導體		絕緣體	單芯		2芯		3芯		4芯		Conductor	Resistance	最小 絕緣電阻
	Area	Construction	Norm. Thick	Norm. Thick	Overall	Norm. Thick	Overall	Norm. Thick	Overall	Norm. Thick	Overall	Resistance	MΩ/KM	
	(mm ²)	(No. /mm)	(mm)	(mm)	Diam. (mm)	(mm)	Diam. (mm)	(mm)	Diam. (mm)	(mm)	Diam. (mm)	Ohm/km/20℃	最大 導體電阻	
	截面積	結構	厚度	厚度	(約)	厚度	(約)	厚度	(約)	厚度	(約)	導體電阻		
2CT	0.75	30/0.18	1.1	1.5	6.4	1.8	10.5	1.8	11.0	1.8	12.0	26.6	1000	
	1.25	50/0.18	1.1	1.6	7.0	1.8	11.5	1.8	12.0	1.9	13.0	16.0	1000	V
	2.0	37/0.26	1.1	1.6	7.3	1.8	12.0	1.9	13.0	2.0	14.0	10.2	1000	V
	3.5	45/0.32	1.1	1.6	8.0	1.9	13.5	2.0	14.5	2.1	16.0	5.54	1000	V
	5.5	70/0.32	1.1	1.7	8.8	2.0	15.0	2.1	16.0	2.2	17.5	3.56	900	V
	8	50/0.45	1.1	1.7	9.4	2.1	16.5	2.2	17.5	2.3	19.5	2.52	800	V
	14	88/0.45	1.4	1.8	11.5	2.3	21	2.4	22	2.6	24	1.43	700	V
	22	7/20/0.45	1.4	2.0	14.0	2.6	26	2.7	27	2.9	30	0.919	600	V
	30	7/27/0.45	1.8	2.1	16.5	2.9	30	3.0	32	3.2	36	0.681	600	V
	38	7/34/0.45	1.8	2.2	17.5	3.0	32	3.2	35	3.4	38	0.541	600	V
	50	19/16/0.45	1.8	2.2	19.0	3.2	35	3.3	38	3.6	42	0.423	500	V
	60	19/20/0.45	1.8	2.3	20	3.4	38	3.5	41	3.8	45	0.339	500	V
80	19/27/0.45	2.3	2.5	24	3.7	44	3.9	48	4.2	53	0.250	500	V	
100	19/34/0.45	2.3	2.6	26	4.0	48	4.2	52	4.5	58	0.199	500	V	